



Decorative Paints and Coatings

Travertino

DESCRIPTION

TRAVERTINO is a mineral-based and natural decorative coating material that provides a travertine aspect on the surface of interior walls.

APPLICATION AREA

On all the interior walls, plaster, gross concrete and timber surfaces; it is used together with its appropriate primer after the surface preparation.

FEATURES

- It enables to create effects with different patterns during the application with applicator's skills
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odor in the application environments with its perfumed feature.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the surfaces where TRAVERTINO will be applied, the surface defects should be corrected SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- TRAVERTINO is applied without dilution, with a stainless steel trowel without dilution so that the first layer thickness will be at least of 1mm.
- Wait minimum 6 hours before applying the second layer
- Before the thorough-drying, you can give the effect on the surface with a special sponge
- In order to obtain a proper finish, the surface should be polished with a steel trowel
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 2-3 hours for touch dry and 48 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- 1 lt covers 1,75 – 2,35 m² of surface
- 1 kg covers 1,00 – 1,35 m² of surface
- The paint consumption for 1 m² area is 425-570 ml and 750-1000 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88



Decorative Paints and Coatings

Travertino

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.017.ENG - Rev01 September 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88