



# Decorative Paints and Coatings

## Vivaldi

### DESCRIPTION

VIVALDI is an acrylic emulsion based interior wall coating material designed to provide velvet-like effect on the surfaces. It contains various additives, fillers and pigments pearlescent.

### APPLICATION AREA

Used on wall, plaster coating, concrete and wood surfaces after surface preparation with the appropriate primer.

### FEATURES

- It creates velvet-like effect on surfaces,
- Resistant to wiping with water,
- It provides shiny look with its rich and bright pigments,
- Due its high vapor permeability, it allows surface to discharge the steam and breathe,
- As it is water-based, it is harmless to human health and environment,
- It provides a pleasant odor in the application environments with its perfumed feature.

### SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR, and painted surfaces should be primed with SAN DECO DECOPRIMER.

### APPLICATION INSTRUCTIONS

- VIVALDI first coat should be applied with steel trowel. After the first coat dries, second coat should be applied again with steel trowel or spatula by applying patch patterns,
- Allow 5 hours between each coats,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

### DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

### THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

- 1 lt covers 4,0 – 6,5 m<sup>2</sup> of surface
- 1 kg covers 4,0 – 6,5 m<sup>2</sup> of surface
- The paint consumption for 1 m<sup>2</sup> area is 150 -250 ml and 150 - 250 gr.

### STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at a temperature between +5°C and +35°C.

### DEKA BOYA SANAYİ ve TİC. A.Ş.



## Decorative Paints and Coatings

# Vivaldi

### HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

### PRECAUTIONARY STATEMENTS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.

**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



#### Product Technical Data Sheet No. DP.004.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

#### DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88